



CMRFID
Technology CO., Ltd

CMRFID (California)

✉ allen@cmrfid.com

☎ +1 213 393 0528

CMRFID (Brazil)

✉ Rinaldo@cmrfid.com

☎ +55 11 964337000

CMRFID (Dubai)

✉ Iman@cmrfid.com

☎ +48 574 549 256

CMRFID (Shanghai)

✉ Javier@cmrfid.com

☎ +86 18601658083

PT160 MICROCHIP READER

Product Introduction

PT160 reader is an brand new product .It uses rechargeable lithium batteries which is more environmentally friendly. It can read all 134.2khz FDX-B tags with a distance of 5-10cm.

Main Parameter	
CPU	ARM(STM32)
working frequency	134.2KHz
buzzer	built-in
screen	24*7 OLED
data storage	NO
Working Manner	
power supply	Lithium battery
communication mode	USB
continuous working time	5 hours
storage temperature	-30°C-65°C
operation humidity	5%~90%
Product Standard	
color	White
G.W.	200g
N.W.	110g
operation temperature	30°C-50°C
Others	
reading standard	ISO11784/5 FDX-B、ID64
international certification	CE, Rohs
guarantee	one year
accessories	Manual book, USB connecting cable(for PT160U)
reading distance	Ear tag: 10cm for FDX-B Microchip : 7cm

