



CMRFID
Technology CO., Ltd

CMRFID (California)

✉ allen@cmrfid.com

☎ +1 213 393 0528

CMRFID (Brazil)

✉ Rinaldo@cmrfid.com

☎ +55 11 964337000

CMRFID (Dubai)

✉ Iman@cmrfid.com

☎ +48 574 549 256

CMRFID (Shanghai)

✉ Javier@cmrfid.com

☎ +86 18601658083

WIND SHIELD TAG (TAMPER PROOF)

Product Introduction

- 860-960 MHz frequency range for worldwide application.
- 3M adhesive instead of traditional bonding
- Good reading performance- good reading distance up to 7M (depending on the reader and environment)
- Uv resistant, anti-solvent
- Tag protocol is EPC class 1 generation 2
- Can read and write data into tag's user memory bank

FEATURES

1. ETC self-service system
2. Smart parking system
3. Logistics and warehousing management
4. Product anti-counterfeiting detection
5. Others: anti-cheating weighing system, the management of transport vehicles, product line management etc.

Specification	
Protocol	EPC class 1 generation 2/ISO 18000-6C
Frequency	860 —960MHZ
Read distance	6-10m (depending on reader and the exact environment)
Anti-collision mechanism	Yes, suitable for cards pool reading (read several cards at same time)
Using area	916+512bits
Read/write	Can read/write data into the tag
Package material	Coated paper
Installation	Easy stick
Storage year	>10years
Wiping times	>100, 000 times
Working temperature	-40°C ~+85°C
Size	45*110MM and customization size is available

